

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations



Printing date: April 14, 2017

Revision: April 14, 2017

1 Identification

- **Product identifier**
- **Trade name:** Rapid Refloor Pit Grout Part A Polyol
- **Product code:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Component of a Control Joint Polyurea System
- **Restrictions on use:** For Professional Use Only
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
 METZGER/McGUIRE
 Mailing Address:
 PO Box 2217
 Concord, NH 03302
 Shipping Address:
 807 Route 3-A
 Bow, NH 03304
 Phone: 603-224-6122
 Toll Free: 800-223-6680
 Email: info@metzgermcguire.com
- **Emergency telephone number:**
 ChemTel Inc.
 (800)255-3924 (North America)
 +1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
 The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**


 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**
 H319 Causes serious eye irritation.
 H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
 P264 Wash thoroughly after handling.
 P280 Wear eye protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

- (Cont'd. of page 1)
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P331 Do NOT induce vomiting.
 - P337+P313 If eye irritation persists: Get medical advice/attention.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Components:**

29253-36-9	Isopropyl-naphthalene	Asp. Tox. 1, H304	35-50%
25214-63-5	Ethylenediamine, propoxylated	Eye Irrit. 2A, H319	25-45%
7631-86-9	precipitated silica (silica - amorphous)		2-6%
13463-67-7	titanium dioxide		1-6%
1333-86-4	carbon black		0.5-2%

- **Additional information:**

Non-classification as a carcinogen is based on non-respirable form of product.
 For the wording of the listed Hazard Statements refer to section 16.
 For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Respiration of particulates is unlikely during normal usage.
 Supply fresh air; consult doctor in case of complaints.
 Provide oxygen treatment if affected person has difficulty breathing.
 In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; immediately call for medical help.
 A person vomiting while lying on their back should be turned onto their side.

- **Most important symptoms and effects, both acute and delayed:**

Breathing difficulty
 Dizziness
 Coughing

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 2)

Causes eye irritation.
Gastric or intestinal disorders when ingested.
Nausea in case of ingestion.
Unconsciousness

Danger:

Danger of impaired breathing.
May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed:

Medical supervision for at least 48 hours.
If swallowed or in case of vomiting, danger of entering the lungs.
If necessary oxygen respiration treatment.
Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Ensure adequate ventilation.
Wear protective equipment. Keep unprotected persons away.
Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 3)

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
Use only receptacles specifically permitted for this substance/product.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizers, strong acids, strong bases.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Keep containers tightly sealed.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

7631-86-9 precipitated silica (silica - amorphous)

NIOSH REL (USA)	Long-term value: 6 mg/m ³
OSHA PEL (USA)	Long-term value: 80 mg/m ³

13463-67-7 titanium dioxide

PEL (USA)	Long-term value: 15* mg/m ³ *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m ³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m ³ *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m ³ A4

1333-86-4 carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
-----------	--

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 4)

REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

Exposure controls
Personal protective equipment:
General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

Engineering controls: No relevant information available.

Breathing equipment:

Not required under normal conditions of use.
 Use suitable respiratory protective device when aerosol or mist is formed.
 For spills, respiratory protection may be advisable.

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:


Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties
Information on basic physical and chemical properties
Appearance:

Form: Liquid
Color: According to product specification
Odor: Slight.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 5)

Odor threshold:	Not determined.
pH-value at 20 °C (68 °F):	10 - 12
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	>176 °C (>349 °F)
Flash point:	>190 °C (>374 °F)
Flammability (solid, gaseous):	Not applicable.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
Oxidizing properties:	Non-oxidizing.
Vapor pressure at 20 °C (68 °F):	<1 mmHg
Density:	
Relative density at 20 °C (68 °F):	1.02-1.05 g/cm ³ (8.512-8.762 lbs/gal)
Vapor density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
Water:	Slightly soluble.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No relevant information available.

10 Stability and reactivity

- Reactivity:** No relevant information available.
- Chemical stability:** Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
Reacts with strong acids and alkali.
Reacts with strong oxidizing agents.
- Conditions to avoid** Excessive heat.
- Incompatible materials** Oxidizers, strong bases, strong acids
- Hazardous decomposition products**
Carbon monoxide and carbon dioxide

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 6)

Nitrogen oxides (NOx)

11 Toxicological information
Information on toxicological effects

- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Slight irritant effect on skin and mucous membranes.
- **On the eye:** Irritating effect.

IARC (International Agency for Research on Cancer):

13463-67-7	titanium dioxide	2B
1333-86-4	carbon black	2B

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.
Eye contact.
Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):** Irritating to eyes.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:**
Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity**
Toxic for aquatic organisms

29253-36-9 Isopropyl-naphthalene

LC50	0.74 mg/l (fish)
EC50	0.15 mg/l (daphnia)

- **Persistence and degradability** Not easily biodegradable
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 7)

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations
Waste treatment methods

- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Uncleaned packagings

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	Not regulated.
· DOT	
· ADR, IMDG, IATA	UN3082
· UN proper shipping name	
· DOT	Not regulated.
· ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isopropyl-naphthalene)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isopropyl-naphthalene), MARINE POLLUTANT
· IATA	Environmentally hazardous substance, liquid, n.o.s. (Isopropyl-naphthalene)
· Transport hazard class(es)	
· DOT	
· Class	Not regulated.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 8)

ADR


· **Class** 9 (M6) Miscellaneous dangerous substances and articles
 · **Label** 9

IMDG, IATA


· **Class** 9 Miscellaneous dangerous substances and articles
 · **Label** 9

Packing group

· **DOT** Not regulated.
 · **ADR, IMDG, IATA** III

Environmental hazards

· **Marine pollutant:** Product contains environmentally hazardous substances: Isopropylinaphthalene
 Yes
 Symbol (fish and tree)

Special precautions for user

Warning: Miscellaneous dangerous substances and articles
 · **Danger code (Kemler):** 90
 · **EMS Number:** F-A,S-F

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional information:

Not regulated when carried in single or combination packaging containing a net quantity of 5 L or less for liquids or 5 kg or less for solids per the following:
 DOT: 171.4(c)(2)
 ADR: SP 375
 IMDG: 2.10.2.7
 IATA: special provision A197

DOT

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 9)

Remarks:

Transport labeling is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

15 Regulatory information
Safety, health and environmental regulations/legislation specific for the substance or mixture

· **United States (USA)**
 · **SARA**

Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed.

Proposition 65 (California)
Chemicals known to cause cancer:

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide
------------	------------------

1333-86-4	carbon black
-----------	--------------

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories
EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide	2B
------------	------------------	----

1333-86-4	carbon black	2B
-----------	--------------	----

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part A Polyol

(Cont'd. of page 10)

NIOSH-Ca (National Institute for Occupational Safety and Health):

13463-67-7 titanium dioxide

1333-86-4 carbon black

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** April 14, 2017 / -

· **Abbreviations and acronyms:**

LDL: Lowest Lethal Dose Observed

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

1 Identification

· **Product identifier**

· **Trade name:** Rapid Refloor Pit Grout Part B ISO

· **Product code:** No other identifiers

· **Recommended use and restriction on use**

· **Recommended use:** Component of a Control Joint Polyurethane System. Caulking and Sealing.

· **Restrictions on use:** For Professional Use Only

· **Details of the supplier of the Safety Data Sheet**

· **Manufacturer/Supplier:**

METZGER/McGUIRE

Mailing Address:

PO Box 2217

Concord, NH 03302

Shipping Address:

807 Route 3-A

Bow, NH 03304

Phone: 603-224-6122

Toll Free: 800-223-6680

Email: info@metzgermcguire.com

· **Emergency telephone number:**

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· **Classification of the substance or mixture**

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS07 GHS08

· **Signal word:** Danger

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 1)

Hazard statements:

- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection.
- P284 In case of inadequate ventilation wear respiratory protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P314 Get medical advice/attention if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Components:

101-68-8	4,4'-methylenediphenyl diisocyanate <ul style="list-style-type: none"> ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 	80-95%
108-32-7	propylene carbonate <ul style="list-style-type: none"> ⚠ Eye Irrit. 2A, H319 	5-20%

Additional information:

For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 2)

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

Description of first aid measures

After inhalation:

- Supply fresh air and to be sure to call for a doctor.
- Provide oxygen treatment if affected person has difficulty breathing.
- In case of irregular breathing or respiratory arrest provide artificial respiration.
- In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

- Immediately remove any clothing soiled by the product.
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.

After eye contact:

- Remove contact lenses if worn.
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

- Rinse out mouth and then drink plenty of water.
- Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

- Asthma attacks
- Headache
- Breathing difficulty
- Coughing
- Allergic reactions
- Irritant to skin and mucous membranes.
- Causes eye irritation.
- May cause respiratory irritation.
- Gastric or intestinal disorders when ingested.
- Nausea in case of ingestion.

Danger:

- Danger of impaired breathing.
- Harmful if inhaled.
- Suspected of causing cancer.
- May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed:

- Contains isocyanates. Consult literature for specific antidotes.
- Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.
- Medical supervision for at least 48 hours.
- If necessary oxygen respiration treatment.
- Later observation for pneumonia and pulmonary edema.
- Treat skin and mucous membrane with antihistamine and corticoid preparations.
- In cases of irritation to the lungs, initial treatment with corticoid steroid inhalants.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Isolate area and prevent access.
- **Environmental precautions**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 4)

- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizers, strong acids, strong bases.
- **Further information about storage conditions:**
Keep containers tightly sealed.
Protect from humidity and water.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL (USA)	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV (USA)	Long-term value: 0.051 mg/m ³ , 0.005 ppm
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin: S
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm
LMPE (Mexico)	Long-term value: 0.005 ppm

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Engineering controls:** No relevant information available.
- **Breathing equipment:**



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 5)

Eye protection:


Safety glasses

Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties
Information on basic physical and chemical properties
Appearance:
Form: Liquid
Color: Yellow

Odor: Faint, aromatic

Odor threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: 5-20 °C (41-68 °F)

Boiling point/Boiling range: >200 °C (>392 °F)

Flash point: >200 °C (>392 °F) (PMCC)

Flammability (solid, gaseous): Not applicable.

Auto-ignition temperature: Not determined.

Decomposition temperature: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits
Lower: Not determined.
Upper: Not determined.

Oxidizing properties: Not determined.

Vapor pressure at 25 °C (77 °F): <0.0001 mmHg

Density:
Relative density: 1.2 g/cm³ (10.014 lbs/gal)

Vapor density: Not determined.

Evaporation rate: Not determined.

Solubility in / Miscibility with
Water: Slowly reacts with water.

Partition coefficient (n-octanol/water): Not determined.

Viscosity
Dynamic: Not determined.

Kinematic: Not determined.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 6)

Other information

No relevant information available.

10 Stability and reactivity
Reactivity: No relevant information available.

Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Exothermic polymerization.

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with strong oxidizing agents.

Conditions to avoid

Moisture.

Excessive heat.

Incompatible materials Oxidizers, strong bases, strong acids

Hazardous decomposition products

Carbon monoxide and carbon dioxide

 Nitrogen oxides (NO_x)

Isocyanate

Hydrogen cyanide (prussic acid)

11 Toxicological information
Information on toxicological effects
Acute toxicity:
LD/LC50 values that are relevant for classification:
101-68-8 4,4'-methylenediphenyl diisocyanate

Oral | LD50 | 2200 mg/kg (mouse)

Primary irritant effect:
On the skin: Irritant to skin and mucous membranes.

On the eye: Irritating effect.

Sensitization: May cause sensitisation by inhalation and skin contact.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 7)

- Eye contact.
- Skin contact.
- **Acute effects (acute toxicity, irritation and corrosivity):**
Harmful if inhaled.
Irritating to eyes, respiratory system and skin.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Carc. 2
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** May cause respiratory irritation.
- **STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 8)

14 Transport information

- **UN-Number**
· DOT, ADR, IMDG, IATA Not regulated.
- **UN proper shipping name**
· DOT, ADR, IMDG, IATA Not regulated.
- **Transport hazard class(es)**
· DOT, ADR, IMDG, IATA
· Class Not regulated.
- **Packing group**
· DOT, ADR, IMDG, IATA Not regulated.
- **Environmental hazards**
· Marine pollutant: No
- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**
- **Section 302 (extremely hazardous substances):**
None of the ingredients are listed.
- **Section 355 (extremely hazardous substances):**
None of the ingredients are listed.
- **Section 313 (Specific toxic chemical listings):**
101-68-8 | 4,4'-methylenediphenyl diisocyanate
- **TSCA (Toxic Substances Control Act)**
All ingredients are listed.
- **Proposition 65 (California)**
- **Chemicals known to cause cancer:**
None of the ingredients are listed.
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients are listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients are listed.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 9)

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories
EPA (Environmental Protection Agency):

101-68-8 | 4,4'-methylenediphenyl diisocyanate | D, CBD

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** April 14, 2017 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LDLo: Lowest Lethal Dose Observed

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017

Revision: April 14, 2017

Trade name: Rapid Refloor Pit Grout Part B ISO

(Cont'd. of page 10)

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com