

Page: 1/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

1 Identification

Product identifier

· Trade name: Rapid Refloor XP Part A Polyol

· Product code: No other identifiers

· Recommended use and restriction on use

· Recommended use: Component of a Control Joint Polyurea System

Restrictions on use: For Professional Use Only

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

METZGER/McGUIRE Mailing Address: PO Box 2217 Concord, NH 03302 Shipping Address:

807 Route 3-A Bow, NH 03304 Phone: 603-224-6122 Toll Free: 800-223-6680

Email: info@metzgermcguire.com

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

Classification of the substance or mixture

Eye Irrit. 2A H319 Causes serious eye irritation.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS0

· Signal word: Warning

· Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Other hazards There are no other hazards not otherwise classified that have been identified.

(Cont'd. on page 2)



Page: 2/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Mixtures

· Componer	· Components:			
25214-63-5	Ethylenediamine, propoxylated	① Eye Irrit. 2A, H319	5-10%	
7631-86-9	precipitated silica (silica - amorphous)		2-6%	
13463-67-7	titanium dioxide	& Carc. 2, H351	1-6%	
1333-86-4	carbon black	& Carc. 2, H351 STOT SE 3, H335	0.5-2%	

Additional information:

Non-classification as a carcinogen is based on non-respirable form of product.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

· After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Causes eye irritation.

Slight irritant effect on skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water stream.

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

(Cont'd. on page 3)

US



Page: 3/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 2)

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

· Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

Precautions for safe handling:

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizers, strong acids, strong bases.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep containers tightly sealed.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

Control parameters

· Components with limit values that require monitoring at the workplace:

7631-86-9 precipitated silica (silica - amorphous)

NIOSH REL (USA) Long-term value: 6 mg/m³

OSHA PEL (USA) Long-term value: 80 mg/m³

13463-67-7 titanium dioxide

(Cont'd. on page 4)



Page: 4/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

		(Cont'd. of page 3)
PEL (USA)	Long-term value: 15* mg/m³ *total dust	
REL (USA) See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³ A4	
1333-86-4 carbon black		
PEL (USA)	Long-term value: 3.5 mg/m³	
REL (USA)	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C	
TLV (USA)	Long-term value: 3* mg/m³ *inhalable fraction	
EL (Canada) Long-term value: 3 mg/m³ IARC 2B		
EV (Canada) Long-term value: 3.5 mg/m³		
LMPE (Mexico)	Long-term value: 3* mg/m³ A3, *fracción inhalable	

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Engineering controls: No relevant information available.

Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

For spills, respiratory protection may be advisable.

Use respiratory protection when grinding or cutting material.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

PVC gloves Neoprene gloves

Nitrile rubber, NBR

(Cont'd. on page 5)



Page: 5/9

(Cont'd. of page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

Eye protection:



Body protection: Protective work clothing

Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties			
Information on basic physical a	Information on basic physical and chemical properties		
Form: Liquid			
Color:	According to product specification		
· Odor:	Slight		
· Odor threshold:	Not determined.		
· pH-value:	10 - 12		
· Melting point/Melting range:	Not determined.		
· Boiling point/Boiling range:	>177 °C (>350.6 °F)		
· Flash point:	>190 °C (>374 °F) (open cup)		
· Flammability (solid, gaseous):	Not applicable.		
Auto-ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits			
Lower:	Not determined.		
Upper:	Not determined.		
· Oxidizing properties:	Not determined.		
· Vapor pressure:	Not determined.		
Density:			
Relative density:	1,02 - 1,05 g/cm³ (8.51-8.76 lbs/gal)		
Vapor density:	Not determined.		
Evaporation rate:	Not determined.		
· Solubility in / Miscibility with			
Water:	Slightly soluble.		
· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity			
Dynamic:	Not determined.		
Kinematic at 40 °C (104 °F):	>20.5 mm²/s		
Other information	No relevant information available.		

(Cont'd. on page 6)



Page: 6/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 5)

10 Stability and reactivity

- Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with catalysts, oxidizing agents and strong alkali.

Reacts with strong acids.

- Conditions to avoid Excessive heat.
- Incompatible materials Oxidizers, strong bases, strong acids
- Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: None.
- Primary irritant effect:
- On the skin: Slight irritant effect on skin and mucous membranes.
- On the eye: Irritating effect.

· IARC (International Agency for Research on Cancer):

13463-67-7	titanium dioxide	2B	
1333-86-4	carbon black	2B	

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

(Cont'd. on page 7)



Page: 7/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 6)

- Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: May be accumulated in organism
- · Mobility in soil: No relevant information available.
- Additional ecological information
- General notes: Avoid release to the environment.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

Waste treatment methods

· Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

Uncleaned packagings

Recommendation: Disposal must be made according to official regulations.

14 Transport information			
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.		
UN proper shipping name DOT, ADR, IMDG, IATA	Not regulated.		
· Transport hazard class(es)			
· DOT, ADR, IMDG, IATA · Class	Not regulated.		
Packing group DOT, ADR, IMDG, IATA	Not regulated.		
Environmental hazards Marine pollutant:	No		
Special precautions for user	Not applicable.		
Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	of Not applicable.		

(Cont'd. on page 8)



Page: 8/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 7)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7 titanium dioxide

1333-86-4 carbon black

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide	2B
1333-86-4	carbon black	2B

NIOSH-Ca (National Institute for Occupational Safety and Health):

13463-67-7 titanium dioxide

1333-86-4 carbon black

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any



Page: 9/9

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: December 01, 2017 Revision: December 01, 2017

Trade name: Rapid Refloor XP Part A Polyol

(Cont'd. of page 8)

specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision December 01, 2017 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Carc. 2: Carcinogenicity - Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets. Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com



Page: 1/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

1 Identification

Product identifier

· Trade name: Rapid Refloor XP Part B ISO

Product code: No other identifiers

Recommended use and restriction on use

Recommended use: Component of a Control Joint Polyurethane System, Caulking and Sealing.

Restrictions on use: For Professional Use Only

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

METZGER/McGUIRE

Mailing Address:

PO Box 2217

Concord, NH 03302

Shipping Address:

807 Route 3-A

Bow. NH 03304

Phone: 603-224-6122

Toll Free: 800-223-6680

Email: info@metzgermcquire.com

Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS07 GHS08

Signal word: Danger

Hazard statements:

H332 Harmful if inhaled.

(Cont'd. on page 2)



Page: 2/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 1)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eve irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

	Growing Grand Grand Contraction Contraction			
ſ	· Components:			
101-68-8 4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H STOT SE 3, H335		Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317;	80-95%	
	108-32-7	propylene carbonate © Eye Irrit. 2A, H319	5-20%	
A delition of information.				

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)



Page: 3/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 2)

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air and to be sure to call for a doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Asthma attacks Breathing difficulty

Coughing

Dizziness

Allergic reactions

May cause respiratory irritation.

Irritating to eyes, respiratory system and skin.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Danger:

Danger of impaired breathing.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed:

Contains isocyanates. Consult literature for specific antidotes.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water stream.

(Cont'd. on page 4)



Page: 4/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 3)

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Additional information: Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Isolate area and prevent access.

Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling

Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Information about protection against explosions and fires:

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

- · Storage
- Requirements to be met by storerooms and receptacles:
- Avoid storage near extreme heat, ignition sources or open flame.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizers, strong acids, strong bases.

Further information about storage conditions:

Keep containers tightly sealed.

Protect from humidity and water.

(Cont'd. on page 5)



Page: 5/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 4)

Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

Control parameters

· Components with limit values that require monitoring at the workplace:				
101-68-8 4,4'-m	101-68-8 4,4'-methylenediphenyl diisocyanate			
PEL (USA)	PEL (USA) Ceiling limit value: 0.2 mg/m³, 0.02 ppm			
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min			
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm			
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S			
EV (Canada) LMPE (Mexico)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm Long-term value: 0.005 ppm			
LIVIF L (IVIEXICO)	Long-term value: 0.003 ppm			

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- Avoid contact with the eyes and skin.
- · Engineering controls: No relevant information available.
- Breathing equipment:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

Body protection: Protective work clothing

(Cont'd. on page 6)



Page: 6/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 5)

Limitation and supervision of exposure into the environment

No relevant information available

9 Physical and chemical properties

Information on basic physical and chemical properties

· Appearance:

Odor threshold:

Form: Liquid
Color: Yellow
Odor: Aromatic

· pH-value: Not determined.

Melting point/Melting range: 5-20 °C (41-68 °F)
Boiling point/Boiling range: >200 °C (>392 °F)

• Flash point: >200 °C (>392 °F) (Pensky-Martens Closed Cup)

Not determined.

· Flammability (solid, gaseous): Not applicable.

Auto-ignition temperature: Not determined.

· **Decomposition temperature:** Not determined.

· Danger of explosion: Product does not present an explosion hazard.

Explosion limits

Lower: Not determined.
Upper: Not determined.
Oxidizing properties: Not determined.

· Vapor pressure at 25 °C (77 °F): <0.0001 mm Hg

Density:

Relative density at 20 °C (68 °F): 1.2 g/cm³ (10.014 lbs/gal)

Vapor density:

Evaporation rate:

Not determined.

Not determined.

Solubility in / Miscibility with

Water: Slowly reacts with water

· Partition coefficient (n-octanol/water): Not determined

· Viscosity

Dynamic: Not determined.

Kinematic: Not determined.

Other information No relevant information available.

10 Stability and reactivity

Reactivity: No relevant information available

(Cont'd. on page 7)



Page: 7/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 6)

Chemical stability: Stable under normal temperatures and pressures.

Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with strong oxidizing agents.

Exothermic reaction.

Conditions to avoid

Moisture.

Excessive heat.

Incompatible materials Oxidizers, strong bases, strong acids

Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

Isocyanate

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

Primary irritant effect:

On the skin: Irritant to skin and mucous membranes.

On the eye: Irritating effect.

Sensitization: May cause sensitisation by inhalation and skin contact.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact

Skin contact.

Acute effects (acute toxicity, irritation and corrosivity):

Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

(Cont'd. on page 8)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 7)

- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: May cause respiratory irritation.
- STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- ·Toxicity
- Aquatic toxicity No relevant information available
- Persistence and degradability No relevant information available.
- Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No relevant information available

13 Disposal considerations

· Waste treatment methods

Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

DOT, ADR, IMDG, IATA Not regulated.

UN proper shipping name

DOT, ADR, IMDG, IATA Not regulated.

(Cont'd. on page 9)



Page: 9/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

		(Cont'd. of page 8)
Transport hazard class(es)		
· DOT, ADR, IMDG, IATA		
Class	Not regulated.	
Packing group		
DOT, ADR, IMDG, IATA	Not regulated.	
Environmental hazards		
· Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Anne	x II of	
MARPOL73/78 and the IBC Code	Not applicable	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

TSCA (Toxic Substances Control Act)

All ingredients are listed.

Proposition 65 (California)

Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories

EPA (Environmental Protection Agency):

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

(Cont'd. on page 10)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: April 14, 2017 Revision: April 14, 2017

Trade name: Rapid Refloor XP Part B ISO

(Cont'd. of page 9)

Page: 10/10

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision April 14, 2017 / -

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB; very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LDLo: Lowest Lethal Dose Observed

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN:

978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com